Configurable Modulator for Pure Phase Modulation

Hong Deng and Wim Bogaerts

Photonics Research Group, Department of Information Technology (INTEC)

Ghent University - IMEC, Gent, Belgium

E-mail: hong.deng@ugent.be

Abstract—We present a configurable silicon modulator for pure phase modulation, implemented as a Mach-Zehnder interferometer with a PN carrier depletion modulator (CDM) and tunable couplers. The spurious intensity modulation introduced by the CDM is compensated by tuning the splitting ratios of the couplers and the phase delay between the arms. In this report, we present the simulation results of this device.

Index Terms—Reconfigurable photonic circuits, modulators, phase modulators

I. INTRODUCTION

Silicon photonics is one of the most promising photonics integrating platforms, useful for a variety of applications. One key component is an electro-optic phase modulator [1]. Silicon carrier-depletion modulators (CDM), realized by embedding a PN junction in a silicon waveguide, are the most common solution for high-speed modulation. A reverse bias over the PN junction changes the refractive index of the waveguide, introducing a phase shift.

However, CDMs suffer from spurious intensity modulation, as the propagation loss also depends on the carrier density. A thermo-optic phase shifter can achieve pure phase modulation, with a limited bandwidth of a few MHz. Here, we report a method to compensate the spurious intensity modulation by embedding the CDM into a configurable circuit. Simulation results show that we can suppress the intensity modulation down to 0.1 dB within a phase change of 0.4π .

II. PRINCIPLE AND SIMULATION

We implement the configurable modulator circuit, shown in Fig. 1, as an MZI with using two tunable couplers (TC). The splitting ratio of the TCs can be tuned from 0% to 100% [2]. One arm contains a CDM, while the other arm contains a phase shifter (PS) to tune the phase delay between the two arms.

The transmission of the MZI is the sum of complex phasors at the end of arms. The CDM will rotate the phasor of the upper arm and also increase its amplitude (with a reverse-biased PN junction); the phasor of the other arm will stay the same. This changing phase delay will therefore change the sum of both phasors. By adjusting their relative amplitude and angle between them, the spurious intensity modulation can be minimized and pure phase modulation can be obtained.

We simulated this circuit, using the $V_\pi \cdot L_\pi$ and voltage-dependent loss of the CDM as described in [3]. Figure 2a shows the simulated intensity modulation (Max/Min) at the output of the circuit as function of the splitting ratio ($TC1=TC2$) and the phase delay, which is the lower the better. Fig. 2b shows the

Fig. 1. Schematic of the reconfigurable modulator. PS: phase shifter; PM: phase modulator; TC: tunable coupler.

voltage response at the operation point highlighted in Fig. 2a. The CDM introduces 1.25 dB intensity modulation and a 0.4π phase modulation with a voltage of 6 V, while the output of the configurable modulator only has 0.1 dB intensity modulation and almost the same 0.4π phase modulation. The trade-off is that the circuit does introduce around 0.5 dB additional loss.

III. CONCLUSION

We reported a configurable modulator for pure phase modulation. Simulation results showed that the 1.25 dB spurious intensity modulation can be suppressed down to 0.1 dB within a phase range of 0.4π .

REFERENCES

- [1] G. T. Reed, G. Mashanovich, F. Y. Gardes, and D. J. Thomson, "Silicon optical modulators," *Nat. Photonics*, vol. 4, no. 8, pp. 518526, Aug. 2010.
- [2] K. Suzuki, G. Cong, K. Tanizawa, S. H. Kim, K. Ikeda, S. Namiki, H. Kawashima, "Ultra-high-extinction-ratio 2x2 silicon optical switch with variable splitter," *Opt. Express*, vol. 23, no. 7, pp. 9086-9092, Apr. 2015.
- [3] H. Yu, M. Pantouvaki, J. Van Campenhout, D. Korn, K. Komorowska, P. Dumon, Y. Li, P. Verheyen, P. Absil, L. Alloati, D. Hillerkuss, "Performance tradeoff between lateral and interdigitated doping patterns for high speed carrier-depletion based silicon modulators," *Opt. Express*, vol. 20, no. 12, pp. 12926-12938, Jun. 2012.

Fig. 2. Simulation results. (a) spurious amplitude modulation for different coupling ratios and phase shifts, (b) Voltage response for the optimal configuration.

Configurable Modulator for Pure Phase Modulation

Publisher: IEEE

2 Author(s) Hong Deng, Wim Bogaerts View All Authors

18
Full
Text Views

Abstract

Abstract:

We present a configurable silicon modulator for pure phase modulation, implemented as a Mach-Zehnder interferometer with a PN carrier depletion modulator (CDM) and tunable couplers. The spurious intensity modulation introduced by the CDM is compensated by tuning the splitting ratios of the couplers and the phase delay between the arms. In this report, we present the simulation results of this device.

Document Sections

- I. Introduction
- II. Principle and Simulation
- III. Conclusion

Authors

Figures

References

Keywords

Published In: 2019 Photonics North (PN)

Date of Conference: 21-23 May 2019

Date Added to IEEE Xplore: 29 August 2019

ISBN Information:

Electronic ISBN: 978-1-7281-3738-4
Print on Demand(PoD) ISBN:
978-1-7281-3739-1

INSPEC Accession Number: 19024719

DOI: 10.1109/PN.2019.8819529

Publisher: IEEE

Conference Location: Quebec City, QC, Canada,
Canada

More Like This

All-optical gating operation in hybrid Si/Si-Mach-Zehnder interferometer
IPRM 2011 - 23rd International Conference on Indium Phosphide and Related Materials
Published: 2011

Silicon Mach-Zehnder Interferometer modulator with PAM-4 data modulation at 64 Gb/s
2015 IEEE 58th International Midwest Symposium on Circuits and Systems (MWSCAS)
Published: 2015

[View More](#)

Top Organizations with Patents on
Technologies Mentioned in This Article