1

2

1. Extended Data

Figure #	Figure title One sentence only	Filename This should be the name the file is saved as when it is uploaded to our system. Please include the file extension. i.e.: <i>Smith_ED_Fig1.jpg</i>	Figure Legend If you are citing a reference for the first time in these legends, please include all new references in the main text Methods References section, and carry on the numbering from the main References section of the paper. If your paper does not have a Methods section, include all new references at the end of the main Reference list.
Extended Data Fig. 1	Example Universal Spectrum Identifiers with explanations	USI_ExtendedFigure1.eps	<p>Example use cases for Universal Spectrum Identifiers (USIs), providing a set of 13 example USIs along with a brief comment on each. These same 13 USIs can be easily viewed as the “Example USIs” select list at http://proteomecentral.proteomexchange.org/usi. Example 4c in Box 1 provides the USI for the demonstrated correct PSM of an ordinary UniProtKB protein Q9UQ35 from Mylonas <i>et al.</i>⁴ Figure 2B (example 4d is the corresponding synthetic peptide spectrum). Example 4a in Box 1 provides the USI for the same spectrum as example 4c, but annotated with the previously, incorrectly reported HLA (Human Leukocyte Antigen) peptide as described in Mylonas <i>et al.</i> Figure 2A. The non-matching synthetic peptide spectrum for the incorrect sequence is given as Box 1 as example 4b. The Human Proteome Project¹⁹ (HPP) has set a high bar for data quality and evidence in support of its goal to provide high-stringency detections for all human proteins. The latest version of its MS data interpretation guidelines 3.0²⁰ have set a requirement that key detection claims of proteins not previously seen via MS must be accompanied by USIs referencing the key spectra for each</p>

			<p>claim, so that the peptide-spectrum matches can be transparently inspected by the community to verify their veracity. For example, the BioPlex dataset¹⁸ was important for detecting novel proteins that had not been previously observed²¹ but it was crucial to consider the provenance of every single identification to exclude all files from experiments where the protein was intentionally overexpressed (as per the standard protocol for analysis of protein-protein interactions). Example 3a in Box 1 provides a PSM derived from a prey protein pulled down as a binding partner to bait protein C5orf38. Example 3b provides a PSM of the same peptide as above, but derived from a recombinant protein used as a bait. This PSM provides a much higher signal-to-noise ratio synthetic peptide reference spectrum as required by HPP guidelines. Illustrating this application of USIs at a community-wide scale, MassIVE further provides an extensive list of USIs for 1,296,916 MassIVE-KB entries in support of HPP Protein Existence (PE) classifications for 16,393 proteins (available at http://massive.ucsd.edu/hpp), including USIs for matching spectra of synthetic peptides (when available in public datasets); an abridged version of this table is also provided as Supplementary Table 1.</p>
--	--	--	--

3 **2. Supplementary Information:**

Item	Present?	Filename This should be the name the file is saved as when it is uploaded to our system, and should include the file extension. The	A brief, numerical description of file contents. <i>i.e.: Supplementary Figures 1-4, Supplementary Discussion, and Supplementary Tables 1-4.</i>

		extension must be .pdf	
Supplementary Information	yes	USI_1.6_Supplementary_Information.pdf	Supplementary Figures S1 – S6
Reporting Summary	yes	nr-reporting-summary.pdf	

4 B. Additional Supplementary Files

Type	Number If there are multiple files of the same type this should be the numerical indicator. i.e. “1” for Video 1, “2” for Video 2, etc.	Filename This should be the name the file is saved as when it is uploaded to our system, and should include the file extension. i.e.: <i>Smith_Supplementary_Video_1.mov</i>
Supplementary Table	1	USI_1.6_Supplementary_table1.xlsx

5

6

7 Universal Spectrum Identifier for mass spectra

8

9 Eric W. Deutsch^{1,*}, Yasset Perez-Riverol², Jeremy Carver³, Shin Kawano⁴, Luis
10 Mendoza¹, Tim Van Den Bossche^{5,6}, Ralf Gabriels^{5,6}, Pierre-Alain Binz⁷, Benjamin
11 Pullman³, Zhi Sun¹, Jim Shofstahl⁸, Wout Bittremieux^{9,10}, Tytus D. Mak¹¹, Joshua
12 Klein¹², Yunping Zhu¹³, Henry Lam¹⁴, Juan Antonio Vizcaíno², and Nuno Bandeira^{3,9,*}

13

14 ¹ Institute for Systems Biology, 401 Terry Ave N, Seattle, WA, 98109, USA

15 ² European Molecular Biology Laboratory, European Bioinformatics Institute (EMBL-
16 EBI), Wellcome Trust Genome Campus, Hinxton, Cambridge CB10 1SD, United
17 Kingdom.

18 ³ Center for Computational Mass Spectrometry, Department of Computer Science and
19 Engineering, Skaggs School of Pharmacy and Pharmaceutical Sciences, University of
20 California, San Diego, 92093-0404, USA

21 ⁴ Toyama University of International Studies, 930-1292 Toyama, Japan

22 ⁵ VIB - UGent Center for Medical Biotechnology, VIB, Ghent, Belgium

23 ⁶ Department of Biomolecular Medicine, Faculty of Medicine and Health Sciences,
24 Ghent University, Ghent, Belgium

25 ⁷ Clinical Chemistry Service, Lausanne University Hospital, 1011 Lausanne, Switzerland

26 ⁸ Thermo Fisher Scientific, 355 River Oaks Parkway San Jose, CA 95134, USA

27 ⁹ Skaggs School of Pharmacy and Pharmaceutical Sciences, University of California San
28 Diego, La Jolla, CA 92093, USA

- ¹⁰ Department of Computer Science, University of Antwerp, 2020 Antwerp, Belgium
¹¹ Mass Spectrometry Data Center, National Institute of Standards and Technology, 100
Bureau Drive, Gaithersburg, MD 20899, USA
¹² Program for Bioinformatics, Boston University, Boston, MA 02215, USA
¹³ National Center for Protein Sciences (Beijing), Beijing Institute of Lifeomics, #38, Life
Science Park, Changping District, Beijing 102206, China
¹⁴ Department of Chemical and Biological Engineering, the Hong Kong University of
Science and Technology, Clear Water Bay, Hong Kong

*Address correspondence to:

Email: edeutsch@systemsbiology.org, Phone: 206-732-1200, Fax: 206-732-1299.

Email: bandeira@ucsd.edu, Phone: 858-534-8666

Keywords: Proteomics Standards Initiative, PSI, mass spectrometry, proteomics,

Universal Spectrum Identifier, USI, standards.

Mass spectra provide the ultimate evidence for supporting the findings of mass
spectrometry (MS) proteomics studies in publications, and it is therefore crucial to be
able to trace the conclusions back to the spectra. The Universal Spectrum Identifier (USI)
provides a standardized mechanism for encoding a virtual path to any mass spectrum
contained in datasets deposited to public proteomics repositories. USIs enable greater
transparency for providing spectral evidence, with more than 1 billion USI identifications
from over 3 billion spectra already available through ProteomeXchange (PX)
repositories.

MS is a major analytical tool for the fields of proteomics and metabolomics among
others, enabling high throughput identification and quantitation of millions of different
analytes including e.g. peptides and small molecules. The availability of proteomics data
in the public domain has increased dramatically in recent years due to the wide adoption
of open data practices in the field, which has been enabled by the reliability of the public

resources that are part of the ProteomeXchange¹ consortium. But while the public availability of the raw mass spectrometry data creates the possibility for scientists to directly inspect whether the data support published results as claimed in the corresponding papers, this remains difficult to implement in practice because there is no standard mechanism supported by the repositories to directly reference individual mass spectra whose interpretations are crucial to the published results. As it stands today, the key spectral evidence for biological studies lacks 'FAIRness' (i.e. Findable, Accessible, Interoperable and Reusable)² and is at best found as a figure in the manuscript or in the supplementary information, which is typically of low quality and does not provide the connection to the raw data (as is required for inspection of the results for the correctness of the corresponding claims). This need becomes even more pressing as the promise of open data for the advancement of science begins to be realized by data reanalyses revealing multiple cases where the data do not support published results^{3,4}. We thus propose a new standardized mechanism supported by PX proteomics repositories for referring to specific spectra of high importance, suitable for citation of data in published manuscripts, as well as for supporting both human interactions and automated access to the data via application programming interfaces (APIs).

A related mechanism for identifying identical metabolomics mass spectra across repositories has been proposed as the SPLASH identifier⁵, an algorithm-generated hash of the spectrum data. SPLASH was designed to determine if the same exact reference spectrum is present in multiple metabolomics resources, since an identical spectrum generates an identical SPLASH identifier. However, (i) SPLASH was based on statistics

of metabolomics spectra that do not apply to proteomics, (ii) requires pre-computing billions of hashes in advance to make them findable and (iii) uses hashes that are not interpretable by humans, and thus is not suitable as a general-purpose identifier for all spectra in proteomics data sets deposited to public repositories.

Here we present an alternative approach using a concatenated multi-part key that specifies the collection, MS run, and index information needed to locate a particular mass spectrum in a repository, defining keys that researchers can easily compose without requiring any special hashing algorithms. This concept has been developed by the Human Proteome Organization⁶ (HUPO) Proteomics Standards Initiative⁷ (PSI) as the USI. It provides a standardized mechanism for identifying a mass spectrum via an abstract path to its location that can be easily mapped to a local path at each resource that contains the spectrum.

The full specification document describing in detail all aspects of version 1.0 of this standard as well as future updates to this specification and information about current implementations with examples are available on the USI page at the PSI web site at <http://psidev.info/usi>. In this letter, we provide a brief overview of the USI's components and describe prominent current applications.

The USI is a multipart key separated by colon characters. The basic form of the USI has five components with an optional sixth as depicted in Figure 1. The first component is the prefix “mzspec” to make clear that the following string is a USI; mzspec is a registered

namespace at identifiers.org⁸ to aid in automated mapping of a USI string to a URL (<https://registry.identifiers.org/registry/mzspec>). The second component is the collection identifier, initially intended to be a PX dataset (PXD) identifier⁹, but can be extended to other types of collection identifiers, and can take on the special value of USI000000 as a placeholder for subsequent dataset submission. The third component is the MS run name, typically the root name of the raw vendor format file or mzML¹⁰ file, either with or without the file extension, depending on the use case as fully described in the specification. The fourth component is a type flag to indicate how to interpret the fifth component; currently allowed values are “scan”, “index”, or “nativeId” (as defined in the mzML 1.1.0 specification available at <http://psidev.info/mzML>). The fifth component is the index value (based on the flag type) within the specified MS run. While these five components can define the abstract path to a spectrum, one additional (sixth) component can specify an interpretation of the spectrum when one is known or proposed. There are many nuances to the specification and the usage of these components that are described in detail in the full specification document.

The spectrum interpretation, depicted as a simple peptide sequence and charge in Figure 1, can become quite complex when taking into account different types of mass modifications, adducts, and non-peptidic molecules, among other scenarios. An entire separate PSI specification, called ProForma 2.0, has been developed to define the rules for representing complex peptidoforms and proteoforms in a standardized manner. The current version is available at the PSI web page <http://psidev.info/proforma>.

There are already several implementations of the USI, and more are emerging. At the spectrum viewer applications of the PX resources PRIDE¹¹, PeptideAtlas¹², MassIVE¹³, jPOST¹⁴, and iProX¹⁵, the USI is displayed for each spectrum viewed when the data set containing the spectrum is associated with a PXD identifier, and these resources also provide a text box in which a USI can be pasted in order to display the requested spectrum (see Online Methods for listing of URLs and a description of the implementations at each site). For convenience, the ProteomeCentral resource of PX implements a single endpoint at <http://proteomecentral.proteomexchange.org/usi/> that reaches out to all participating partners to fetch spectra for a provided USI if available at any resource. It also provides USI validator functionality, which checks that the format of the USI complies with the USI specification. An overview of the USI ecosystem is depicted in Figure 2.

Since the USI is designed as a virtual path to a spectrum based on a set of rules and conventions, there is no need to compute hashes for billions of existent spectra or newly generated spectra like in the case of the SPLASH identifier. Implementing repositories need only map the virtual path components (collection, MS run, indexType) to their local storage system to make the spectra findable and accessible. As a key point, USIs can be retroactively determined for spectra deposited long ago to a PX repository (the spectrum depicted in Figure 1 was deposited in 2013). Furthermore, authors of new publications can easily construct and provide within their articles references to key spectra that support their conclusions by knowing the collection identifier (typically known as a manuscript is being submitted), the MS run filename, and spectrum scan number, which

are usually determinable from within most analysis environments. PX repositories also provide various tools to assist with the process of generating USIs for dataset spectra (see Online Methods). Within some proteomics analysis workflows, the provenance information about the original scan numbers is unfortunately lost during processing, but the importance of provenance is now well understood and any such loss of provenance should be remedied in future software revisions. See Extended Data Figure 1 for a set of 12 example USIs with extended descriptions.

USI provides a standardized mechanism for encoding a virtual path to any spectrum contained in data sets deposited to public repositories or contained in public spectral libraries. Current PX data repositories have implemented support for USIs as part of the submission or browsing process as described in the Online Methods. It has been primarily designed for the proteomics community, but could easily be adopted by the metabolomics community (and potentially others) if there is a will to do so (the current USI specification already supports non-proteomics spectra but additional guidelines would be needed for instance to represent non-proteomics identifications). It enables greater transparency and data ‘FAIRness’² for providing spectral evidence in support of key findings in publications and public data, and provides a standardized mechanism for communicating identifiers of specific spectra among software applications. We thus expect that USIs will become a fundamental mechanism supporting open science across all fields of research supported by MS data.

Notes

The authors declare no competing financial interest.

Acknowledgements

This work was funded in part by the National Institutes of Health grants R01GM087221, R24GM127667, 1R01LM013115 and P41GM103484, and National Science Foundation grants 1933311, 1922871 and ABI 1759980. JAV wants to acknowledge Wellcome Trust grant number 208391/Z/17/Z, BBSRC BB/S01781X/1, BB/P024599/1 and the partnering grants BB/N022440/1 and BB/N022432/1. SK wants to acknowledge the Database Integration Coordination Program from the National Bioscience Database Center, Japan Science and Technology Agency [18063028] and the Japan Society for the Promotion of Science KAKENHI [JP20H03245]. We also would like to acknowledge the Research Foundation – Flanders (SB grant 1S90918N to TVDB; SB grant 1S50918N to RG; WB is a postdoctoral researcher).

Data availability statement

No datasets were generated or analyzed during the current study.

Code availability statement

No custom code was used to analyze data, but code used to fetch spectra using USIs is publicly available in GitHub at <https://github.com/proteomexchange/proteomecentral>.

References

1. Deutsch, E. W. *et al.* The ProteomeXchange consortium in 2020: enabling ‘big data’ approaches in proteomics. *Nucleic Acids Res.* **48**, D1145–D1152 (2020).
2. Wilkinson, M. D. *et al.* The FAIR Guiding Principles for scientific data management and stewardship. *Sci. Data* **3**, 160018 (2016).
3. Ezkurdia, I., Vázquez, J., Valencia, A. & Tress, M. Analyzing the first drafts of the human proteome. *J. Proteome Res.* **13**, 3854–3855 (2014).
4. Mylonas, R. *et al.* Estimating the Contribution of Proteasomal Spliced Peptides to the HLA-I Ligandome. *Mol. Cell. Proteomics MCP* **17**, 2347–2357 (2018).
5. Wohlgemuth, G. *et al.* SPLASH, a hashed identifier for mass spectra. *Nat. Biotechnol.* **34**, 1099–1101 (2016).
6. Hanash, S. & Celis, J. E. The Human Proteome Organization: a mission to advance proteome knowledge. *Mol. Cell. Proteomics MCP* **1**, 413–414 (2002).
7. Deutsch, E. W. *et al.* Development of data representation standards by the human proteome organization proteomics standards initiative. *J. Am. Med. Inform. Assoc. JAMIA* **22**, 495–506 (2015).

- 220 8. Wimalaratne, S. M. *et al.* Uniform resolution of compact identifiers for biomedical
221 data. *Sci. Data* **5**, 180029 (2018).
- 222 9. Deutsch, E. W. *et al.* The ProteomeXchange consortium in 2017: supporting the
223 cultural change in proteomics public data deposition. *Nucleic Acids Res.* **45**, D1100–
224 D1106 (2017).
- 225 10. Martens, L. *et al.* mzML--a community standard for mass spectrometry data. *Mol.*
226 *Cell. Proteomics MCP* **10**, R110.000133 (2011).
- 227 11. Perez-Riverol, Y. *et al.* The PRIDE database and related tools and resources in 2019:
228 improving support for quantification data. *Nucleic Acids Res.* **47**, D442–D450 (2019).
- 229 12. Desiere, F. *et al.* The PeptideAtlas project. *Nucleic Acids Res.* **34**, D655–658 (2006).
- 230 13. Wang, M. *et al.* Assembling the Community-Scale Discoverable Human Proteome.
231 *Cell Syst.* **7**, 412–421.e5 (2018).
- 232 14. Moriya, Y. *et al.* The jPOST environment: an integrated proteomics data repository
233 and database. *Nucleic Acids Res.* **47**, D1218–D1224 (2019).
- 234 15. Ma, J. *et al.* iProX: an integrated proteome resource. *Nucleic Acids Res.* **47**, D1211–
235 D1217 (2019).
- 236 16. Kim, M.-S. *et al.* A draft map of the human proteome. *Nature* **509**, 575–581 (2014).
- 237 17. Zhou, J.-Y. *et al.* Quality Assessments of Long-Term Quantitative Proteomic
238 Analysis of Breast Cancer Xenograft Tissues. *J. Proteome Res.* **16**, 4523–4530
239 (2017).
- 240 18. Huttlin, E. L. *et al.* The BioPlex Network: A Systematic Exploration of the Human
241 Interactome. *Cell* **162**, 425–440 (2015).

- 242 19. Omenn, G. S. *et al.* Research on The Human Proteome Reaches a Major Milestone:
243 >90% of Predicted Human Proteins Now Credibly Detected, according to the HUPO
244 Human Proteome Project. *J. Proteome Res.* (2020)
245 doi:10.1021/acs.jproteome.0c00485.
- 246 20. Deutsch, E. W. *et al.* Human Proteome Project Mass Spectrometry Data
247 Interpretation Guidelines 3.0. *J. Proteome Res.* **18**, 4108–4116 (2019).
- 248 21. Pullman, B. S., Wertz, J., Carver, J. & Bandeira, N. ProteinExplorer: A Repository-
249 Scale Resource for Exploration of Protein Detection in Public Mass Spectrometry
250 Data Sets. *J. Proteome Res.* **17**, 4227–4234 (2018).

251

252

Figure 1: (A) Graphical overview of the general format of the USI, including the mzspec prefix, the collection component, the MS run component, the indexType, the indexNumber, and the optional interpretation. (B) A USI example using the spectrum scan number, once with and once without the optional spectrum interpretation. (C) Visual representation of this spectrum (mzspec:PXD000561:Adult_Frontalcortex_bRP_Elite_85_f09:scan:17555:VLHPLEGA VVIIFK/2) in ProteomeCentral, accompanied with the ion table indicating the m/z values of the identified b- and y-ions. The Lorikeet spectrum viewer is used.

Online Methods

List of resources and their URLs that allow a user to copy-paste a USI into the web page and visualize the spectrum if it is available

Resource	URL
ProteomeCentral	http://proteomecentral.proteomexchange.org/usi/
jPOST	https://repository.jpostdb.org/spectrum/
MassIVE	http://massive.ucsd.edu/ProteoSAFe/usi.jsp
PeptideAtlas	https://db.systemsbiology.net/sbeams/cgi/PeptideAtlas/ShowObservedSpectrum
PRIDE	https://www.ebi.ac.uk/pride/archive/spectra
ProteomicsDB	https://www.proteomicsdb.org/use/
GNPS (metabolomics)	https://gnps.ucsd.edu/ProteoSAFe/gnps_usi.jsp
iProX	https://www.iprox.org/page/spectrum.html

USI Implementation notes from each resource

ProteomeCentral

ProteomeCentral hosts a web-based USI validator and resolver at <http://proteomecentral.proteomexchange.org/usi/>. Users of this web page may paste a USI into a text box and choose either to validate or fetch the spectrum/PSM encoded in the USI. Validation is performed by a back-end service that parses the supplied USI and decomposes it into its various components and ensures that they are well formed and follow the rules of the specification. Collection identifiers are checked to ensure that they encode a supported namespace, but not that they are within a valid range. MS runs components are separated but not checked as essentially any string is permitted. The indexType is checked for a valid value. The indexNumber is separated but not checked against the relevant file to ensure that it is within range. The interpretation string is parsed to ensure it is well formed and that controlled vocabulary (CV) terms are present in the relevant CVs. The service returns the decomposed and interpreted USI and a flag to indicate if it is valid or not. A well-formed USI may not actually correspond to a spectrum, but this cannot be determined without asking all resources to look up the USI.

The USI lookup function first validates the provided USI as described above, and then, if valid, sends the USI to all participating resource services that can provide spectra given a USI. USI lookups are performed in parallel within the JavaScript. A result table depicts the results from the participating resources as they arrive in real time. The first spectrum to return from one of the resources is sent to an embedded Lorikeet spectrum viewer in the page with basic defaults for an HCD MS/MS spectrum, along with the peptide interpretation, if provided. The user may click on various hyperlinks in the table to see the spectrum obtained from different resources, link out to the resources themselves, where the user can explore the spectrum using the native tools at the resource, as well as access additional information about the returned spectrum data. The USI lookup service may be triggered automatically without required copy-paste with a URL <http://proteomecentral.proteomexchange.org/usi/?usi=<USI>> where the <USI> is replaced with an actual USI, e.g. <http://proteomecentral.proteomexchange.org/usi/?usi=mzspec:PX000561:Adult Frontal cortex bRP Elite 85 f09:scan:17555:VLHPLEGAVVIFK/2>.

jPOST

jPOST provides a USI resolver at <https://repository.jpostdb.org/spectrum/>. Currently there are 27M spectra corresponding to USIs. Spectra submitted by "Complete Submission" are basically available via USI. In addition, spectra submitted to PX partners other than jPOST will also provide USI from jPOST in the case of frequently used datasets.

313

314 **MassIVE**

315 The main MassIVE interface for resolution of USIs is available at
316 <https://massive.ucsd.edu/ProteoSAFe/usi.jsp>. At the time of writing, MassIVE can
317 resolve USIs for over >3.3 billion spectra in >10,000 datasets. In addition, MassIVE can
318 also resolve USIs to >580 million Peptide Spectrum Matches (PSMs), including both
319 PSMs that were included in complete dataset submissions (reported with PXD and MSV
320 accessions) and PSMs derived by MassIVE (and third-party) reanalysis of public datasets
321 (reported with RPXD and RMSV accessions). As illustrated in Figure S1, USIs can be
322 entered in a text box and can be used to search MassIVE datasets in four different ways.
323 Each of the four different types of search is accompanied by a small blue icon containing
324 a short description of each type of search, as well as listing an example USI illustrating
325 the types of results for each search.

326

327 The first option (“Search MassIVE spectra”, also illustrated in Figure S1) is to search for
328 the dataset and spectrum file(s) as specified in the USI
329 [mzspec:PXD000561:Adult_Frontalcortex_bRP_Elite_85_f09:scan:17555:VLHPLEGAV](#)
330 [VIIFK/2](#). If successful, this search returns a table with one row per spectrum file with a
331 matching file name. Clicking on the spectrum icon (on the left) for rows corresponding to
332 spectrum files in standard open formats will open a new panel allowing for visualization
333 and interactive exploration of the USI spectrum. If a peptide annotation is included in the
334 USI then it is used to label and color spectrum peaks according to the theoretical masses
335 of the standard fragment ion types.

336

337 The second option (“Search all MassIVE PSMs”) is to search all of MassIVE for other
338 possible identifications for the spectrum indicated in the USI. Since spectrum files can be
339 resubmitted in multiple datasets and reanalyzed in multiple RPXD/RMSV reanalyses,
340 this option searches for all occurrences of MassIVE PSMs matching the USI spectrum
341 file and spectrum identifier (e.g., scan number). The example in Figure S2(a) shows that
342 the initial spectrum identification ([mzspec:PXD002041:TCGA-AA-3518-01A-](#)
343 [11_W_VU_20120915_A0218_3F_R_FR04:scan:9649:ADNQRLKDENGALIR/2](#))
344 reported in a proteogenomics search for a CPTAC dataset is actually a worse match to the
345 spectrum than the alternative identification to a different peptide found in MassIVE
346 reanalyses with a common N-term modification of +28 Da (likely Formylation, a
347 common sample handling artefact), a type of modification that was not considered in the
348 original paper.

349

350 The third option (“Search MassIVE-KB reference spectra”) searches the [MassIVE](#)
351 [Knowledge Base \(MassIVE-KB\)](#) for reference spectra for the same peptide as in the USI.
352 Reference spectra can include spectra of synthetic peptides as well as spectra selected as
353 representatives in the MassIVE-KB spectral library. As shown in Figure S2(b), the
354 spectrum in the USI
355 [mzspec:PXD004452:20150410_QE3_UPLC9_DBJ_SA_46fractions_Rep1_18:scan:2873](#)
356 [:PAPTLEEEKIR/2](#) was incorrectly identified to a peptide whose reference spectrum

shows a distinct fragmentation pattern than that of the synthetic peptide reported in this search.

The fourth option (“Search Protein Explorer proteins”) searches [MassIVE’s Protein Explorer](#) for human proteins containing the USI peptide sequence. As shown in Figure S2(c), the peptide in the USI [mzspec:PXD000865:00644_H11_P004899_B0P_A00_R1:scan:3727:PAGDGTFQK/2](#) maps to 6 distinct HLA proteins.

To facilitate the generation of supplementary materials support the review process for the manuscripts associated with ProteomeXchange datasets, MassIVE also enables exporting identification results in TSV format including USIs for all selected results. This is described and illustrated in Figure S3.

PeptideAtlas

PeptideAtlas provides access to over 1 billion spectra via the USI mechanism. Users can go directly to <https://db.systemsbiology.net/sbeams/cgi/PeptideAtlas/ShowObservedSpectrum> and copy-paste a USI. If the dataset is housed at PeptideAtlas, then the system dynamically finds the location of the dataset on PeptideAtlas disks, finds the mzML.gz file corresponding to the requested MS run, and then extracts the requested spectrum from the mzML.gz file. Part of the PeptideAtlas processing pipeline is to download raw vendor files from the original hosting repositories and convert them to mzML.gz via msconvert or ThermoRawFileReader and these are all stored in an accessible manner. The extracted spectrum is then displayed with the requested annotation embedded in the USI if there is one.

Additionally, as users are browsing the PeptideAtlas web interface, if they click on a link to view a PSM in a PeptideAtlas build, if the dataset has a PXD identifier (not all datasets in PeptideAtlas do), then a USI for that PSM is created and displayed above the spectrum.

PRIDE

At the time of writing, the PRIDE database provides access to over 540 million peptide-spectrum matches (PSMs) originally submitted by researchers in the PRIDE Archive Spectra resource (<https://www.ebi.ac.uk/pride/archive/spectra>). Users can search by USIs, which enables them to find specific PSMs from submitted data.

In addition, a peptide sequence search can be performed in the search-box, which enables users to find PSMs across the entire resource. A list of PSMs is shown (Figure S4)

including peptide sequences, post-translational modifications, search engine scores, charge, and two additional columns that highlight whether the PSM has passed or not the original analysis threshold and PRIDE internal pipelines thresholds (e.g. PSM FDR < 0.1).

The accession column in the result table provides a direct link to the project centric page which contains the information of the original submitted dataset, including the results details page. If users perform a search using a USI (e.g. [https://www.ebi.ac.uk/pride/archive/spectra?usi=mzspec:PXD000966:CPTAC_CompRef_00_iTRAQ_12_5Feb12_Cougar_11-10-11.mzML:scan:11850:\[UNIMOD:214\]YYWGGLYSWDMSK\[UNIMOD:214\]/2](https://www.ebi.ac.uk/pride/archive/spectra?usi=mzspec:PXD000966:CPTAC_CompRef_00_iTRAQ_12_5Feb12_Cougar_11-10-11.mzML:scan:11850:[UNIMOD:214]YYWGGLYSWDMSK[UNIMOD:214]/2)), the corresponding spectra will be shown in the spectrum panel below in the same page.

It is possible to access and visualise any PSM included in a publicly available “complete” PRIDE dataset. To do that, users need to go to <https://www.ebi.ac.uk/pride/archive/spectra> and search for a particular peptide sequence.

For instance, for the peptide sequence WQLVGITSWGEGCAR, the resulting URL is: <https://www.ebi.ac.uk/pride/archive/spectra?peptideSequence=WQLVGITSWGEGCAR> (Figure S5). At that point it is possible to select all PSMs containing that particular sequence in a given dataset (Figure S6).

ProteomicsDB (Universal Spectrum Explorer)

The ProteomicsDB team has developed a web tool called Universal Spectrum Explorer (USE - <https://www.proteomicsdb.org/use/>) [DOI:10.1101/2020.09.08.287557v1]; to query and visualize public spectra using USIs from multiple archives including PRIDE and PeptideAtlas. In addition, USE can retrieve real-time prediction of tandem mass spectra from the deep learning framework Prosit. The query spectra from public USI or provided by the user can be exported from USE as editable scalable high quality vector graphics (e.g., [https://www.proteomicsdb.org/use/?usi=mzspec:PXD015890:18May18_Olson_WT2.raw%20\(F001551\).mzid_18May18_Olson_WT2.raw_\(F001551\).MGF:index:6913:AEAEA_QAEELSFP/2&usi_origin=pride](https://www.proteomicsdb.org/use/?usi=mzspec:PXD015890:18May18_Olson_WT2.raw%20(F001551).mzid_18May18_Olson_WT2.raw_(F001551).MGF:index:6913:AEAEA_QAEELSFP/2&usi_origin=pride)).

443

444 **GNPS (metabolomics)**

445 GNPS hosts the Metabolomics Spectrum Resolver tool at
446 https://gnps.ucsd.edu/ProteoSAFe/gnps_usi.jsp [DOI:10.1101/2020.05.09.086066] to
447 access metabolomics mass spectra available in MassIVE/GNPS and alternative
448 metabolomics data repositories. Besides spectra deposited to GNPS
449 [DOI:10.1038/nbt.3597], the Metabolomics Spectrum Resolver builds upon the USI
450 standard to resolve spectra from other popular metabolomics data resources, such as
451 MetaboLights [DOI:10.1093/nar/gks1004], Metabolomics Workbench
452 [DOI:10.1093/nar/gkv1042], MassBank [DOI:10.1002/jms.1777], MoNA, and MS2LDA
453 [DOI:10.1093/bioinformatics/btx582] to provide a universal interface to more than 450
454 million metabolomics spectra. The Metabolomics Spectrum Resolver can display
455 individual spectra or display two spectra in a mirror plot to evaluate their similarity.
456 Additionally, it supports linking back to the source spectra in their original data resources
457 to allow users to explore the original context of the spectra and computes SPLASH
458 identifiers [DOI:10.1038/nbt.3689] to enable comparisons of spectra across different
459 resources.

460

461

462

463

464 **iProX**

465 iProX provides USI search and display at <http://www.iprox.org/page/spectrum.html> for 6
466 million spectra in the HBase. The result file of the "complete submission" project in
467 iProX are parsed into spectra records uniquely marked by USIs and stored in the HBase.
468 There is also a backup mechanism to ensure data reliability.

469

470

Figure 2. Graphical depiction of USI application ecosystem. Members of the community can uniquely identify spectra from journal articles and other sources using USIs. A USI can be resolved potentially at any of several different repositories that store datasets, or spectra can be obtained and viewed using independent applications, such as at ProteomeCentral, which store no spectra themselves, but can fetch spectral data from repositories using USIs. Hundreds of millions of peptide-spectrum matches (PSMs) and spectra without matches are accessible via USIs at the various repositories. PSMs or spectra can even be uniquely identified with QR (Quick Response) codes.

Extended Data Figure 1. Example use cases for Universal Spectrum Identifiers (USIs), providing a set of 13 example USIs along with a brief comment on each. These same 13 USIs can be easily viewed as the “Box 1 example USIs” select list at <http://proteomecentral.proteomexchange.org/usi>. Example 4c in Box 1 provides the USI for the demonstrated correct PSM of an ordinary UniProtKB protein Q9UQ35 from Mylonas *et al.*⁴ Figure 2B (example 4d is the corresponding synthetic peptide spectrum). Example 4a in Box 1 provides the USI for the same spectrum as example 4c, but annotated with the previously, incorrectly reported HLA (Human Leukocyte Antigen) peptide as described in Mylonas *et al.* Figure 2A. The non-matching synthetic peptide spectrum for the incorrect sequence is given as Box 1 as example 4b. The Human Proteome Project¹⁹ (HPP) has set a high bar for data quality and evidence in support of its goal to provide high-stringency detections for all human proteins. The latest version of its MS data interpretation guidelines 3.0²⁰ have set a requirement that key detection claims of proteins not previously seen via MS must be accompanied by USIs referencing the key spectra for each claim, so that the peptide-spectrum matches can be transparently inspected by the community to verify their veracity. For example, the BioPlex dataset¹⁸ was important for detecting novel proteins that had not been previously observed²¹ but it was crucial to consider the provenance of every single identification to exclude all files from experiments where the protein was intentionally overexpressed (as per the standard protocol for analysis of protein-protein interactions). Example 3a in Box 1 provides a PSM derived from a prey protein pulled down as a binding partner to bait protein C5orf38. Example 3b provides a PSM of the same peptide as above, but derived from a recombinant protein used as a bait. This PSM provides a much higher signal-to-noise ratio synthetic peptide reference spectrum as required by HPP guidelines. Illustrating this application of USIs at a community-wide scale, MassIVE further provides an extensive list of USIs for 1,296,916 MassIVE-KB entries in support of HPP Protein Existence (PE) classifications for 16,393 proteins (available at <http://massive.ucsd.edu/hpp>), including USIs for matching spectra of synthetic peptides (when available in public datasets); an abridged version of this table is also provided as Supplementary Table 1.

(A) General format

mzspec:<collection>:<msRun>:<indexType>:<indexNumber>:<optionalInterpretation>

(B) Dataset spectrum example using native scan number, with and without optional interpretation

mzspec:PXD000561:Adult_Frontalcortex_bRP_Elite_85_f09:scan:17555
mzspec:PXD000561:Adult_Frontalcortex_bRP_Elite_85_f09:scan:17555:VLHPLEGAVVIIFK/2

prefix collection msRun component index scan spectrum
 component (file root of .raw or .mzML) flag number interpretation

(C) Visualization in ProteomeCentral

VLHPLEGAVVIIFK, MH+ 1534.9356, m/z 767.9714

File: VLHPLEGAVVIIFK/2, Scan: 17555, Exp. m/z: 767.9700, Charge: 2

mzspec:PXD000561:Adult_Frontalcortex_bRP_Elite_85_f09:scan:17555

File: VLHPLEGAVVIIFK/2, Scan: 17555, Exp. m/z: 767.9700, Charge: 2

[illegible]

PRIDE Archive
Proteomics IDentifications Database

470 M PSMs
470 M spectra

MassIVE

580 M PSMs
3 B spectra

27 M PSMs
27 M spectra

334 M PSMs
1 B spectra

Case 1: Typical identification of an unmodified peptide in support of protein identification (one spectrum, simple interpretation, no mass modifications)

mzspec:PXD000561:Adult_Frontalcortex_bRP_Elite_85_f09:scan:17555:VLHPLEGAVVIFK/2

Example 1: Peptide Spectrum Match (PSM) of an unmodified doubly-charged peptide VLHPLEGAVVIFK from the Kim et al.¹⁶ draft human proteome dataset. Most of the intense unannotated peaks are internal fragmentation ions of this peptide.

Case 2: Flexible notation for reporting identification of post-translational modifications (one spectrum, interpretation with Unimod names, Unimod identifiers, PSI-MOD names and PSI-MOD identifiers for mass modifications)

mzspec:PXD000966:CPTAC_CompRef_00_iTRAQ_05_2Feb12_Cougar_11-10-09.mzML:scan:12298:[iTRAQ4plex]-LHFFM[Oxidation]PGFAPLTSR/2

Example 2a: PSM of a iTRAQ4plex-labeled peptide from a CPTAC CompRef dataset¹⁷, with modifications specified using Unimod names. Using names rather than accession numbers or mass deltas is the recommended notation since it precisely identifies the modification while also being easily interpretable.

mzspec:PXD000966:CPTAC_CompRef_00_iTRAQ_05_2Feb12_Cougar_11-10-09.mzML:scan:12298:[UNIMOD:214]-LHFFM[UNIMOD:35]PGFAPLTSR/2

Example 2b: Same CPTAC PSM with modifications specified using Unimod accession numbers. This notation is equally precise but not as easily readable as modification names.

mzspec:PXD000966:CPTAC_CompRef_00_iTRAQ_05_2Feb12_Cougar_11-10-09.mzML:scan:12298:[MOD:01499]-LHFFM[L-methionine sulfoxide]PGFAPLTSR/2

Example 2c: Same CPTAC PSM with modifications specified using PSI-MOD names and accession numbers.

mzspec:PXD000966:CPTAC_CompRef_00_iTRAQ_05_2Feb12_Cougar_11-10-09.mzML:scan:12298:[+144.1021]-LHFFM[+15.9949]PGFAPLTSR/2

Example 2d: Same CPTAC PSM with modifications specified using mass offsets. This notation is generally discouraged when the type of modification is known in advance, but is the only available option to report results of open modification searches returning algorithmically-detected uninterpreted mass offsets.

Case 3: Supporting evidence of translated gene products (i.e., protein existence) as detected in public datasets, including matches to spectra of synthetic peptides as required by the HUPO Human Proteome Project (HPP) guidelines for detection of novel proteins

mzspec:PXD022531:j12541_C5orf38:scan:12368:VAATLEILTLK/2

Example 3a: Identification derived from a prey protein (Q5VTA0) in the Huttlin et al.¹⁸ BioPlex dataset, pulled down as a binding partner to bait protein C5orf38. With only this single identification, this protein remains an HPP missing protein since a single identification does not meet HPP guidelines.

mzspec:PXD022531:b11156_PRAMEF17:scan:22140:VAATLEILTLK/2

Example 3b: PSM of the same peptide as above, but derived from a recombinant protein used as a bait in the Huttlin et al. BioPlex dataset. This PSM provides a much higher signal-to-noise ratio synthetic peptide reference spectrum as required by HPP guidelines.

Case 4: Data reanalysis refuting previous claims of novel HLA (Human Leukocyte Antigen) peptides

mzspec:PXD000394:20130504_EXQ3_MiBa_SA_Fib-2:scan:4234:SGVSRKPAPG/2

Example 4a: Identification originally used to reported a novel HLA peptide (Mylonas et al.⁴ Figure 2A).

mzspec:PXD010793:20170817_QEh1_LC1_HuPa_SplicingPep_10pmol_G2_R01:scan:8296:SGVSRKPAPG/2

Example 4b: Spectrum of a synthetic peptide for the same peptide SGVSRKPAPG/2 revealing a distinctively different fragmentation pattern from example 4a.

mzspec:PXD000394:20130504_EXQ3_MiBa_SA_Fib-2:scan:4234:ATASPPRQK/2

Example 4c: The same spectrum as for example 4a, but correctly identified to commonly-occurring peptide from UniProtKB protein Q9UQ35 (Mylonas et al. Figure 2B).

mzspec:PXD010793:20170817_QEh1_LC1_HuPa_SplicingPep_10pmol_G2_R01:scan:7452:ATASPPRQK/2

Example 4d: Spectrum of a synthetic peptide for ATASPPRQK/2 (same as 4c) with a fragmentation pattern matching example 4c, thus confirming the identification to protein Q9UQ35.

Case 5: Reporting spectra of unidentified peptides with the potential to lead to interesting new discoveries

mzspec:PXD010154:01284_E04_P013188_B00_N29_R1.mzML:scan:31291

Example 5a: Unidentified peptide detected by clustering as highly abundant only in Small intestine and Duodenum out of 29 human tissues in PXD010154.

mzspec:PXD010154:01284_E04_P013188_B00_N29_R1.mzML:scan:31291:DQNGTWEM[Oxidation]ESNENFEGYM[Oxidation]K/2

Example 5b: Manual annotation of the spectrum from example 5a reveals it to be a multiply-modified version of a peptide previously detected only as unmodified.